

# DuoPASS

Fingerprint Total Solution Provider

*Fingerprint & RFID Time & Attendance /  
Access Control*



# DuoPASS

Incorporating one's own advanced fingerprint recognition algorithm, DuoPASS offers a perfect solution for Access Control and Time & Attendance. With high quality fingerprint and RFID authentication, DuoPASS provides a different level of reliability and convenience. Versatile communication options including RS232, RS485, Wiegand and TCP/IP enable easy network integration and data transfer.

DuoPASS offers industry-leading technology with high speed fingerprint recognition and sophisticated touchpad design and enable simple and easy operation in various languages for worldwide users.

## ● FEATURES

- **Advanced Fingerprint Quality**  
Own fingerprint algorithm guarantees fast and reliable fingerprint reading quality
- **13.56MHz or 125KHz RFID Module**  
Include 13.56MHz or 125KHz RFID module in a terminal. RFID card recognition enhances double layer security level with fingerprint.
- **Touchpad Design**  
Touchpad made of polycarbonate has higher resistance against water, dirt and shock. Sophisticated touchpad design tempts users visually.
- **RS232, RS485, TCP/IP**  
Support RS232, RS485, Wiegand and TCP/IP optionally.
- **3000 Users / 8000 Logs**  
Maximum 3000 users and 8000 logs can be stored in a terminal, and 3000 fingerprints can be identified in a second.
- **Excellent & Easy Program**  
Excellent data management by access control and Time & Attendance program. Enable users to see access control and Time & Attendance report via simple and easy operation.
- **Multiple Languages**  
Support multiple languages including Korean, Japanese, English and Spanish for worldwide users.
- **Back Light LCD**  
LCD with Back Light enables easy and accurate operation possible (Blue-negative colored LCD).

## ● APPLICATION

- Access control
- Time attendance



## ● SPECIFICATION

Fingerprint FAR/FRR	0.0001% / 0.1%
Fingerprint Verification Time	< 1 sec
RFID Reader	13.56MHz(Mifare), ISO14443A or 125KHz(EM)
User / Log Event	3,000(Including RFID) / 8,000(Option: 16,000)
Communications	RS232, RS485, Wiegand, TCP/IP(Option)
Door Lock Control	COM, NO, NC (Relay SPDT)
LCD Display	16 Characters x 2 Lines (Blue Negative)
Touch Keypad	16Key(12 Normal / 4 Function)
Voltage / Current	12VDC / Max 500mA
Operating temperature	0°C~60°C
Dimensions	150(W)×156(H)×46(D)mm
Weight (gr.)	300g

※ This specification is subject to change without prior notice.

### DIGENT Co., Ltd.

11th F, Gangnam Center Bldg., #825-13 Yeoksam1-dong, Gangnam-gu, Seoul, 135-934, Korea  
Tel : +82-2-3420-3111 Fax : +82-2-3420-3009 Web : www.digent.com

**DIGENT**